

CESAB PRODUCT RANGE





Counterbalanced and Warehouse Equipment



Powered stacker trucks







S110 - 110S

-  1.0 t
-  1960 mm
-  24V / 63 Ah
-  Integrated batteries and charger. S110S: straddle support arm variant.







S210 - 212 - 214

-  1.0 t - 1.2 t - 1.4 t
-  4755 mm
-  24V / 300 Ah
-  Optional operator platform available.







S215 - 216 - 220

-  1.45 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Available with a choice of chassis width.







S208L

-  0.8 t
-  1580 mm
-  24V / 230 Ah
-  Can lift up to 2000 kg when lifting with the support arms only. Available with optional automatic height adjustment.







S212L - 214L

-  1.2 t - 1.4 t
-  4755 mm
-  24V / 300 Ah
-  Elevating support arms. Optional operator platform available.







S215L - 216L - 220L

-  1.45 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Elevating support arms.



S220D

-  1.0 t
-  2100 mm
-  24V / 300 Ah
-  Double stacker, lifts 800 + 1200 kg lifting with forks + support arms or 2000 kg when lifting with the support arms only. Optional operator platform available.







S212S

-  1.2 t
-  4755 mm
-  24V / 300 Ah
-  Straddle support arms. Optional operator platform also available.







S214S

-  1.4 t
-  5400 mm
-  24V / 500 Ah
-  Straddle support arms.







S312 - 314 - 316 - 320

-  1.2 t - 1.4 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Available with a choice of speeds up to 10km/h.







S312L - 314L - 316L - 320L

-  1.2 t - 1.4 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Elevating support arms. Available with a choice of speed, up to 10km/h.



S314S

-  1.4 t
-  5350 mm
-  24V / 500 Ah
-  Straddle support arms.